


Announcing the **NEW** ZP Express Program



Receive our most popular ZP temperature and/or humidity chambers in just 6-8 weeks. You can even select from common options listed below.

Applicable Models

Single Stage: -34°C to +190°C 208/230V, 1/3 Ph, 60 Hz.	Cascade: -70°C to +190°C 208/230V, 1/3 Ph, 60 Hz.	Tundra: -45°C to +190°C 208/230V, 3 Ph, 60 Hz.
Temperature Chambers ZPE-8-2-SC/AC ZPE-16-2-SC/AC ZPE-32-2-SC/AC	Temperature Chambers ZPE-8-2-2-SC/AC ZPE-16-2-2-SC/AC ZPE-32-2-2-SC/AC	Temperature Chambers ZPE-8-3.5-SCT/AC ZPE-16-3.5-SCT/AC ZPE-32-3.5-SCT/AC
Temperature/Humidity Chambers ZPHE-8-2-SC/AC ZPHE-16-2-SC/AC ZPHE-32-2-SC/AC	Temperature/Humidity Chambers ZPHE-8-2-2-SC/AC ZPHE-16-2-2-SC/AC ZPHE-32-2-2-SC/AC	Temperature/Humidity Chambers ZPHE-8-3.5-SCT/AC ZPHE-16-3.5-SCT/AC ZPHE-32-3.5-SCT/AC

Options Available

- Recirculating water option
- Dry air purge system
- Demineralizer cartridge
- LN2 boost
- Rear top vent exhaust
- Water pressure regulator
- Sound deadening
- Reverse osmosis
- Shelves
- EZ View
- Low humidity
- Extended warranty
- Product High/Low Limit



Notes:

Shipping 6-8 weeks from order acknowledgment
 Please consult factory for quantity orders of the same model
 Not applicable to 50 Hz. Models

Weiss Technik North America, Inc.
 Cincinnati Facility
 12011 Mosteller Road
 Cincinnati, OH 45241

(p) 513-326-5252

(f) 513-326-5258

www.cszindustrial.com

CSZ
Cincinnati Sub-Zero
The Testing Standard.